



PASCHIM GUJARAT VIJ COMPANY LIMITED

REGD. & CORPORATE OFFICE:- "PASCHIM GUJARAT VIJ SEVA SADAN"

OFF NANA MAVA MAIN ROAD, LAXMINAGAR, RAJKOT-360004

CIN U40102GJ2003SGC042908

Telephone Nos:-0281-2380425/427/2360182

Fax No:-0281-2368175

Website:-www.pgvcl.com

E-mail:-proc.pg@gebmail.com

Specifications of Industrial Safety Shoes

Sr.no	Particular	Specification
	Certification	IS 15298 PART (II)
1	Upper leather	Full Grain Barton Non Din leather.
2	Upper leather thickness	1.8 mm- 2.20 mm +/- 0.2 mm
3	Toe	Composite Toe cap as per Standard. Impact resistance of toe cap should be 200 Joules
4	Sole	P.U. Single Density: Oil-acid-alkali resistant
5	Sole Fixation	Direct Injection Process
6	Sole hardness (RHD)	50-60 +/- 5 shores.
7	Heel material	PU with special composition.
8	Sole thickness	35 mm +/- 05 mm(Heel) 20 mm +/- 5 (At forepart)
9	Thread.	Nylon or Polyester 20 No & 40 No & 60 No
10	Eyelet	Nos. of Eye lets should be Four
11	Lace	Nylon 80 cm round with breaking strength 50-60 kg (Black colour)
12	Height of shoe (Bottom of head to top of ankle)	For size 8 - 95 mm(+/- 5 mm)
	Design	Better gripping in rough terrain with anti-skid feature. Diamond shaped Cleats with optimum contact area. Strategically located to transfer the body weight to the ground. Sole Design specially for self - cleaning on every step by flushing out mud & sludge Special high density foam cushioned collar to provide comfort at ankle area for longer duration usage.
13	Weight	Weight of a pair of safety shoes should not be more than 900 gms
14	Color	Black
15	Finishing	Elegant and Spray finish
16	Packing	One shoe box & further 12 such boxes in a corrugated carton
17	Size roll	5-12 English for Male & 3-7 for female
18	IS No.	Each shoes must contain ISI marking as per
19	Electrical resistance test	No breakdown/flashover at 12 KV AC.
20	Others	Ensure comfortable level high during long & continuous working to the person. Wear & tear resistant can withstand rough usage also.
21	Guarantee	One year

Signature of Tenderer:

Date:

Place:

Company's Round Seal:



PASCHIM GUJARAT VIJ COMPANY LIMITED

REGD. & CORPORATE OFFICE:- "PASCHIM GUJARAT VIJ SEVA SADAN"

OFF NANA MAVVA MAIN ROAD, LAXMINAGAR, RAJKOT-360004

CIN U40102GJ2003SGC042908

Telephone Nos:-0281-2380425/427/2360182

Fax No:-0281-2368175

Website:-www.pgvcl.com

E-mail:-proc.pg@gebmail.com

- The bidder has to submit copy of invoice for Direct Injection Process Machine.
- The bidder has to submit the test certificate of various tests as per IS 15298 (Part-II):2011 from approved lab. [ClauseNo.5: Basic Requirement for "Safety Footwear" of IS 15298 (Part-II):2011] along with test of electrical resistance of 12KV from any approved lab (FDDI - Noida OR ERDA.)
- **PGVCL reserves right to carry out any test/s as per relevant IS/Specification on tender sample.**
- Note:- The Size Roll (i.e. 5-12 English for Male & 3-7 for Female mentioned at Sr. no.-17 in specification) in tender, (i.e. English (UK) size) and marking on shoes will be according English standard too, all bidders have to offer material as per English (UK) size standard and marking."

Signature of Tenderer:		Company's Round Seal:
Date:	Place:	